



STTG-W 15



STTG-S 30 bzw. STTG-S 15



Self-closing valve (optional)

Changes which serve the technical improvement will be maintained by us! Errors excepted!

Boot/ Clog Dryer, type STTG-W

Made of stainless steel 1.4301

Warm-air-blowing dryer for wall-mounting

- Capacity: 10, 15 or 20 pairs of boots/ clogs
- For wall-mounting
- Hygienic Design according to HACCP guidelines
- Solid stainless steel tubular frame construction
- Drying due to warm-air-blower
- Day-time switch as well as switch "hand – or – auto"
- Completely welded and stained

Boot-/Clog Dryer, type STTG-W

Type	Capacity	Dimensions W x D x H in mm	Article- No:
STTG-W 10	10 pairs	790 x 485 x 1930	10000223
STTG-W 15	15 pairs	1110 x 485 x 1930	10000224
STTG-W 20	20 pairs	1430 x 485 x 1930	10000225

Other dimensions on request, delivery without boots/ clogs

Options and technical data: please see below



Boot/ Clog Dryer, type STTG-S

Made of stainless steel 1.4301

Warm-air-blowing dryer as standing version

- Capacity: 10, 15, 20, 30 or 60 pairs of boots/ clogs
- Stand version with height-adjustable feet
- Hygienic Design according to HACCP guidelines
- Solid stainless steel tubular frame construction
- Drying due to warm-air-blower
- Day-time switch as well as switch "hand – or – auto"
- Completely welded and stained

Boot-/Clog Dryer, type STTG-S

Type	Capacity	Dimensions W x D x H in mm	Article- No:
STTG-S 10	10 pairs	790 x 485 x 2080	10000226
STTG-S 15	15 pairs	1110 x 485 x 2080	10000229
STTG-S 20	20 pairs	1430 x 485 x 2080	10000239
STTG-S 30	30 pairs	2070 x 485 x 2080	10000264
STTG-S 60	60 pairs	2220 x 680 x 2080	10000265

Other dimensions on request, delivery without boots/ clogs

Technical Data:

Performance: 1x1000 Watt (STTG-S 60: 2 x 1000 W)

Power supply: 1x230 V/N/PE (1,5m connection cable)

Protection class: IP 54

Options:

- Self-closing valve (ventilation valve), Article-No: 16000005
- Ozone-generator (1,2 kW), Article-No: 99900026
- Week-time switch on request