



HKV, execution: right, mobile



HKV, execution: left, stationary



Slot cover roll-up for critical areas (pharmaceutical industries)

Lift and tilt systems, type HKV

Made of stainless steel 1.4301



For Bins according to DIN 9797

- Scaffold, Lifting pillar, body completely made of stainless steel
- Solid construction ensures a long durability
- Optional stationary or with chassis
- Mechanic safety-appliance
- Manufactured according to CE-norm, EU and USDA conform

The execution of the HKV depends on the bulk goods and is expended by special chutes or lifting platforms if necessary. The HKV could be tailored for nearly every application.

The HKV could be equipped with a chassis for tilting heights up to 2050mm.

Lift and tilt systems, type HKV			
Type	Tilting height mm	Execution	Article-No.
HKV-1550L	1050 x 1550	Left	18003000
HKV-1550R	1050 x 1550	Right	18006000
HKV-2050L	1550 x 2050	Left	18003001
HKV-2050R	1550 x 2050	Right	18006001
HKV-2550L	2050 x 2550	Left	18003002
HKV-2550R	2050 x 2550	Right	18006002
HKV-3050L	2550 x 3050	Left	18003003
HKV-3050R	2550 x 3050	Right	18006003
HKV-3550L	3050 x 3550	Left	18003004
HKV-3550R	3050 x 3550	Right	18006004
HKV-4050L	3550 x 4050	Left	18003005
HKV-4050R	3550 x 4050	Right	18006005
HKV-4550L	4050 x 4550	Left	18003006
HKV-4550R	4050 x 4550	Right	18006006

Options: ● Chassis, Article-No: 18003007

- Slot cover roll-up

Technical Data:

Power supply: 400 V; 50 Hz

Performance: 0,75 kW

Loading capacity: 300 kg

Lifting speed: 5 m/min

Adjustability: 5 stufig in 100 mm Schritten

Protection class: IP 65 (Motor & Schaltkasten)

