

MAXIMUS RE

The most compact thermoformer available!




PACKAGING MADE SIMPLE. THE COMPACT **SOLUTION FOR YOUR GROWING BUSINESS!**

The Maximus RE is the ideal solution for small production environments with limited space. Thanks to its compact design and integrated control cabinet, it enables a space-saving setup and maximum efficiency. The intuitive 10-inch HMI Panel ensures precise process monitoring, while the standard film width of 420 mm and 6 different stroke lengths support versatile applications. Its well-thought-out design allows for dual-sided use at the loading area, further enhancing user convenience.

- · 2.200 mm length x 750 mm width, < 1,7 m² footprint
- · 6 different stroke lengths allow different and versatile applications
- · Integrated electrical cabinet for space-saving footprint
- · Loading area usable from both sides
- · 10-inch HMI panel, swiveling (IP67)
- · Emergency stop switch on both sides of the machine
- · Short delivery times thanks to efficient pre-assembly







MAXIMUS RE

Technical Info | Available Options

Electrical side strip upwind

· Film width: 420 mm

· Available stroke lengths: 200 / 230 / 260 / 280 / 300 / 320 mm

· Maximum draw depth: 90 mm

2.1 (always included) · Format:

· Packaging types: Sealing, Vacuum, MAP (flexible film)

Output:

· Electrical voltage: 3 x 230 V N/PE | 3 x 400 V N/PE | 50/60 Hz | IP65

max. 6 cycles/min.

min. 6 bar · Compressed air:

· Vacuum pump: 063 cbm/h (internal)





Available options:

Gas flush | 100 cbm/h Vacuum pump Machine on casters | Change format Photo cell control for registered top web Perimeter sealing plates | Cooling unit

Available devider sets



EASY TO CONFIGURE | FULL-FEATURED | COMPACT

→ Top film unwind HMI-Panel Bottom film unwind ° Loading area Cutting area .--Sealing station ← Forming station . Cooling unit (optional) Vacuum pump electrical cabinet

